US007744643B2

(12) **United States Patent**
Hegg

(10) **Patent No.: US 7,744,643 B2**
(45) **Date of Patent: Jun. 29, 2010**

(54) **DISPLACEABLE STENT SIDE BRANCH STRUCTURE**

(75) Inventor: **Jens Hegg**, Minneapolis, MN (US)

(73) Assignee: **Boston Scientific Scimed, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 98 days.

(21) Appl. No.: **11/417,466**

(22) Filed: **May 4, 2006**

(65) **Prior Publication Data**

US 2007/0260303 A1 Nov. 8, 2007

(51) **Int. Cl.**
A61F 2/06 (2006.01)

(52) **U.S. Cl.** **623/1.35**

(58) **Field of Classification Search** 623/1.15–1.17, 623/1.22, 1.35
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,013,091	A	1/2000	Ley et al.	606/191
6,017,363	A	1/2000	Hojeibane	623/1
6,030,414	A	2/2000	Taheri	623/1
6,033,433	A	3/2000	Ehr et al.	623/1
6,048,361	A	4/2000	Von Oepen	623/1
6,056,775	A	5/2000	Borghi et al.	623/1.16
6,129,754	A	10/2000	Kanesaka et al.	623/1
6,210,429	B1	4/2001	Vardi et al.	623/1.11
6,258,116	B1	7/2001	Hojeibane	623/1.16
6,290,673	B1	9/2001	Shanley	604/102.02
6,325,826	B1	12/2001	Vardi et al.	623/1.35
6,334,870	B1	1/2002	Ehr et al.	623/1.16
6,361,555	B1	3/2002	Wilson	623/1.11
6,428,570	B1 *	8/2002	Globerman	623/1.15
6,436,134	B2	8/2002	Richter et al.	673/1.15
6,579,309	B1	6/2003	Loos et al.	623/1.16
6,582,394	B1	6/2003	Reiss et al.	604/96.01
6,695,877	B2	2/2004	Brucker et al.	623/1.16
6,706,062	B2	3/2004	Vardi	623/1.15
6,749,628	B1	6/2004	Callol et al.	623/1.15

(Continued)

FOREIGN PATENT DOCUMENTS

WO	2004026180	4/2004

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 11/300,210, filed Dec. 14, 2005, Eidenschink et al.

Primary Examiner—Suzette J Gherbi
(74) *Attorney, Agent, or Firm*—Vidas, Arrett & Steinkraus, P.A.

(57) **ABSTRACT**

In at least one embodiment, a stent comprises a side branch structure having an inner crown, an outer crown and a plurality of side branch connectors, each side branch connector connecting between the inner crown and the outer crown. Upon expansion of the side branch structure, the inner crown displaces outwardly in a stent radial direction. The entire inner crown moves out of the area defined by the generally cylindrical framework of the main stent body. Upon the outward displacement of the inner crown, the side branch connectors may reorient and also extend out of the area defined by the generally cylindrical framework of the main stent body. The inner crown may further comprise a plurality of outwardly deployable petals. Desirably, side branch expansion forces placed on the inner crown will first cause the inner crown to displace outwardly, then cause the petals to deploy outwardly.

17 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS

6,835,203	B1	12/2004	Vardi et al.	623/1.34
6,955,687	B2	10/2005	Richter et al.	623/1.35
7,341,598	B2 *	3/2008	Davidson et al.	623/1.35
2001/0056297	A1	12/2001	Hojeibane	623/1.16
2002/0035392	A1	3/2002	Wilson	623/1.11
2002/0193873	A1	12/2002	Brucker et al.	623/1.35
2003/0195606	A1 *	10/2003	Davidson et al.	623/1.11
2004/0138737	A1	7/2004	Davidson et al.	623/1.35
2004/0267352	A1	12/2004	Davidson et al.	623/1.15
2005/0010278	A1	1/2005	Vardi et al.	623/1.15
2005/0060027	A1	3/2005	Khenansho et al.	623/1.35
2005/0102023	A1	5/2005	Yadin et al.	623/1.15
2005/0119731	A1	6/2005	Brucker et al.	623/1.35
2005/0131526	A1	6/2005	Wong	623/1.15
2005/0154444	A1	7/2005	Quadri	623/1.13

FOREIGN PATENT DOCUMENTS

WO	2005009295	2/2005

* cited by examiner


10
12
11
2
1
14
16
17
18
20
21
22
23
24
26
28
30
36
38
40
42
46
48
50
56
60
63
64
65
66
68
70
86
88
90

FIG. 1


10
11
12
14
16
17
18
20
21
22
23
24
26
28
30
36
38
40
42
44
46
48
50
52
54
61
62
64
66
68
70
76
78
80
86
88
90
λ

FIG. 2



FIG. 3



FIG. 4



FIG. 5



FIG. 6



FIG. 7



FIG. 8



FIG. 9



FIG. 10

DISPLACEABLE STENT SIDE BRANCH STRUCTURE

CROSS-REFERENCE TO RELATED APPLICATIONS

Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH

Not Applicable

BACKGROUND OF THE INVENTION

1. Field of the Invention

In some embodiments this invention relates to implantable medical devices, their manufacture, and methods of use. Some embodiments are directed to delivery systems, such as catheter systems of all types, which are utilized in the delivery of such devices.

2. Description of the Related Art

A stent is a medical device introduced to a body lumen and is well known in the art. Typically, a stent is implanted in a blood vessel at the site of a stenosis or aneurysm endoluminally, i.e. by so-called "minimally invasive techniques" in which the stent in a radially reduced configuration, optionally restrained in a radially compressed configuration by a sheath and/or catheter, is delivered by a stent delivery system or "introducer" to the site where it is required. The introducer may enter the body from an access location outside the body, such as through the patient's skin, or by a "cut down" technique in which the entry blood vessel is exposed by minor surgical means.

Stents, grafts, stent-grafts, vena cava filters, expandable frameworks, and similar implantable medical devices, collectively referred to hereinafter as stents, are radially expandable endoprostheses which are typically intravascular implants capable of being implanted transluminally and enlarged radially after being introduced percutaneously. Stents may be implanted in a variety of body lumens or vessels such as within the vascular system, urinary tracts, bile ducts, fallopian tubes, coronary vessels, secondary vessels, etc. Stents may be used to reinforce body vessels and to prevent restenosis following angioplasty in the vascular system. They may be self-expanding, expanded by an internal radial force, such as when mounted on a balloon, or a combination of self-expanding and balloon expandable (hybrid expandable).

Stents may be created by methods including cutting or etching a design from a tubular stock, from a flat sheet which is cut or etched and which is subsequently rolled or from one or more interwoven wires or braids.

Within the vasculature it is not uncommon for stenoses to form at a vessel bifurcation. A bifurcation is an area of the vasculature or other portion of the body where a first (or parent) vessel is bifurcated into two or more branch vessels. Where a stenotic lesion or lesions form at such a bifurcation, the lesion(s) can affect only one of the vessels (i.e., either of the branch vessels or the parent vessel) two of the vessels, or all three vessels. Many prior art stents however are not wholly satisfactory for use where the site of desired application of the stent is juxtaposed or extends across a bifurcation in an artery or vein such, for example, as the bifurcation in the mammalian aortic artery into the common iliac arteries.

There remains a need for novel stent designs capable of supporting both a parent vessel and a branch vessel.

The art referred to and/or described above is not intended to constitute an admission that any patent, publication or other information referred to herein is "prior art" with respect to this invention. In addition, this section should not be construed to mean that a search has been made or that no other pertinent information as defined in 37 C.F.R. §1.56(a) exists.

U.S. Pat. No. 6,706,062 to Vardi et al. is incorporated herein by reference in its entirety. U.S. patent application Ser. No. 11/300,210 is incorporated herein by reference in its entirety. All other US patents, US applications and all other published documents mentioned anywhere in this application are also incorporated herein by reference in their entirety.

Without limiting the scope of the invention a brief summary of some of the claimed embodiments of the invention is set forth below. Additional details of the summarized embodiments of the invention and/or additional embodiments of the invention may be found in the Detailed Description of the Invention below.

A brief abstract of the technical disclosure in the specification is provided as well only for the purposes of complying with 37 C.F.R. 1.72. The abstract is not intended to be used for interpreting the scope of the claims.

BRIEF SUMMARY OF THE INVENTION

In at least one embodiment, a stent comprises a plurality of struts arranged to form a substantially cylindrical expandable framework. The struts further define a plurality of cells and a side branch structure comprising an outer crown, an inner crown and a plurality of side branch connectors. The outer crown comprises a plurality of outer crown struts arranged to form a closed loop, the outer crown defining a side branch area. The inner crown comprises a plurality of inner crown struts arranged to form a closed loop, the inner crown defining an inner side branch cell having a shape different from the shape of any other cell. Each side branch connector has a first end connected to the inner crown and a second end connected to the outer crown. Upon expansion of said side branch structure, the entire inner crown displaces outwardly from said cylindrical expandable framework in a stent radial direction.

In at least one other embodiment, a stent comprises a plurality of struts arranged to form a substantially cylindrical expandable framework. The struts further define a plurality of cells and a side branch structure comprising an outer crown, an intermediate crown, an inner crown, a plurality of outer side branch connectors and a plurality of inner side branch connectors. The outer crown comprises a plurality of outer crown struts arranged to form a closed loop, the outer crown defining a side branch area. The intermediate crown comprises a plurality of intermediate crown struts arranged to form a closed loop, the intermediate crown oriented within the outer crown. Each outer side branch connector has a first end connected to the intermediate crown and a second end connected to the outer crown. The inner crown comprises a plurality of inner crown struts arranged to form a closed loop, the inner crown defining an inner side branch cell having a shape different from the shape of any other cell, the inner crown oriented within the intermediate crown. Each inner side branch connector has a first end connected to the inner crown and a second end connected to the intermediate crown. Upon a first expansion step of said side branch structure, the entire inner crown displaces outwardly from said cylindrical expandable framework in a stent radial direction. In some embodiments, the entire intermediate crown displaces outwardly from said cylindrical expandable framework in a stent radial direction upon said first expansion step. In some

embodiments, the entire inner crown displaces outwardly from said intermediate crown in a stent radial direction during a second expansion step.

The stents may be placed with in a bodily vessel at a bifurcation and expanded to support the vessel(s). In some embodiments, the inner crown and side branch connectors, when expanded, extend into a bifurcation or branch vessel and provide scaffolding support to the branch vessel.

The invention further comprises methods of expanding the side branch structure of stents as described herein.

These and other embodiments which characterize the invention are pointed out with particularity in the claims annexed hereto and forming a part hereof. However, for a better understanding of the invention, its advantages and objectives obtained by its use, reference can be made to the drawings which form a further part hereof and the accompanying descriptive matter, in which there are illustrated and described various embodiments of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of the invention is hereafter described with specific reference being made to the drawings.

FIG. **1** shows an embodiment of a flat pattern for a stent.

FIG. **2** shows another embodiment of a flat pattern for a stent.

FIG. **3** shows another embodiment of a flat pattern for a stent.

FIG. **4** shows a stent according to the embodiment of FIG. **1** with the side branch structure unexpanded.

FIG. **5** shows the stent of FIG. **4** with the side branch structure in an expanded state.

FIG. **6** shows the stent of FIG. **4** with the side branch structure expanded and the side branch petals outwardly deployed.

FIG. **7** shows a stent according to the embodiment of FIG. **3** with the side branch structure unexpanded.

FIG. **8** shows the stent of FIG. **7** with the side branch structure partially expanded.

FIG. **9** shows the stent of FIG. **7** with the side branch structure in an expanded state.

FIG. **10** shows the stent of FIG. **7** with the side branch structure expanded and the side branch petals outwardly deployed.

DETAILED DESCRIPTION OF THE INVENTION

While this invention may be embodied in many different forms, there are described in detail herein specific embodiments of the invention. This description is an exemplification of the principles of the invention and is not intended to limit the invention to the particular embodiments illustrated.

For the purposes of this disclosure, like reference numerals in the figures shall refer to like features unless otherwise indicated.

In some embodiments, a stent **10** comprises an outwardly expandable side branch structure that includes a crown structure having a plurality of outwardly deployable petals. The entire crown structure may displace radially outwardly from the main body portion of the stent **10**, and the petals may then deploy outwardly.

Each of FIGS. **1-3** shows an embodiment of a flat pattern for a stent **10** having an outwardly expandable side branch structure **40**. Each embodiment of a stent **10** comprises a plurality of strut members arranged to form a substantially cylindrical expandable framework. Each stent **10** embodiment has a proximal end **12**, a distal end **14** and includes a plurality of serpentine bands **20**. Each serpentine band **20** includes a plurality of struts **22**, each strut **22** having a first end **21** and a second end **23**. Circumferentially adjacent struts **22** within a serpentine band **20** are connected by turns **28**. Turns **28** located on a proximal side of a serpentine band **20** comprise proximal peaks **24**, and turns **28** located on a distal side of a serpentine band **20** comprise distal troughs or valleys **26**.

Serpentine bands **20** which are adjacent to one another along the length of the stent **10** are connected by at least one connector strut **16**. In some embodiments, a connector strut **16** may span between turns **28** of adjacent serpentine bands **20**. For example, a first end **17** of a connector strut **16** may connect to a distal valley **26** of one serpentine band **20**, and a second end **18** of the connector strut **16** may connect to a proximal peak **24** of an adjacent serpentine band **20**.

Connector struts **16** may connect to any portion of a serpentine band **20**, such as a turn **28**, or in some embodiments, a strut **22**. In some embodiments, a connector strut **16** may be linear or straight along its length. In some embodiments, a connector strut **16** may include curvature along its length, and may further include multiple portions of curvature, for example a convex portion and a concave portion that may be connected at an inflection point.

In some embodiments, a stent **10** may comprise a first type of connector strut **36** and a second type of connector strut **38**. A first connector strut **36** may extend in a first direction. The first connector strut **36** may be oriented at a first angle to a stent lengthwise axis **11**. A second connector strut **38** may extend in a second direction that is different than or non-parallel to the first direction. In some embodiments, the first angle and the second angle may have the same magnitude but different orientations.

A stent **10** may have any suitable number of serpentine bands **20**. Each serpentine band **20** may have any suitable number of struts **22**. In some embodiments, a serpentine band **20** may have a wavelength λ or distance between repeating elements of the serpentine band **20**. For example, a wavelength λ may comprise a distance between adjacent proximal peaks **24** of a serpentine band **20**, or a distance between adjacent distal valleys **26** of a serpentine band **20**. In some embodiments, the wavelength λ may change between adjacent serpentine bands **20**. For example, the wavelength λ of various serpentine bands **20** may be the shortest for serpentine bands **20** located near the center of the stent **10**, and may increase as the stent **10** is traversed toward either end **12**, **14**. Adjacent serpentine bands **20** may further comprise different numbers of struts **22** and different numbers of turns **28**.

In some embodiments, a serpentine band **20** extends about an entire circumference of the stent **10**. For example, serpentine bands **20** that are offset from the side branch structure **40** may generally extend about an entire circumference of the stent **10**. In some embodiments, a serpentine band **20** extends about a portion of a circumference of the stent **10**. For example, serpentine bands **20** that connect to the side branch structure **40** may extend about a portion of a circumference of the stent **10**.

A stent **10** may further comprise a plurality of cells **30**. A cell **30** may comprise an opening in the stent **10** expandable framework between serpentine bands **20** and connector struts **16**. In some embodiments, a cell **30** may be bounded by a serpentine band **20**, a connector strut **16**, another serpentine band **20** and another connector strut **16**.

Referring to FIG. **1**, a stent **10** may further comprise a side branch structure **40**, which may define an inner crown **42**, an outer crown **46** and a plurality of side branch connectors **60**. The side branch structure **40** may be generally centered about a side branch center point **64**. The inner crown **42** may define

an inner side branch cell **50** which may be shaped differently than any other cell **30** of the stent **10**. The inner side branch cell **50** may be generally centered upon the side branch center point **64**.

The inner crown **42** may have any suitable shape and may form a closed loop that extends around the side branch center point **64**. In some embodiments, the inner crown **42** may comprise a plurality of inner crown struts **66** connected between alternating inner crown inner turns **68** and inner crown outer turns **70**. The inner crown inner turns **68** are located closer to the side branch center point **64** than the inner crown outer turns **70**.

In some embodiments, each inner crown inner turn **68** may be aligned about a reference circle centered upon the side branch center point **64**, and each inner crown outer turn **70** may be aligned upon another reference circle centered upon the side branch center point **64**. Thus, each inner crown inner turn **68** may be located the same distance from the side branch center point **64** as all other inner crown inner turns **68**, and each inner crown outer turn **70** may be located the same distance from the side branch center point **64** as all other inner crown outer turns **70**.

In some embodiments, a peak of an inner crown inner turn **68** may point radially inwardly toward the side branch center point **64**. A peak of an inner crown outer turn **70** may point radially outwardly away from the side branch center point **64**.

Each inner crown strut **66** is connected at one end to an inner crown inner turn **68** and at another end to an inner crown outer turn **70**. Each inner crown strut **66** may be straight along its length and may be oriented substantially parallel to a side branch radial direction.

The inner crown **42** defines a plurality of petals **48**, each petal **48** comprising two inner crown struts **66** connected by an inner crown inner turn **68**. Each petal **48** may unfold outwardly upon expansion of the side branch structure **40** and deployment of said petals **48** as described herein below and illustrated, for example, in FIGS. **5-6** and **9-10**.

The outer crown **46** may have any suitable shape and may form a closed loop that extends around the inner crown **42**. The outer crown **46** may be centered about the side branch center point **64**.

In some embodiments, the outer crown **46** may comprise a plurality of outer crown struts **86** connected between alternating outer crown inner turns **88** and outer crown outer turns **90**. Each outer crown strut **86** is connected at one end to an outer crown inner turn **88** and at another end to an outer crown outer turn **90**. Each outer crown strut **86** may be straight along its length. Each outer crown strut **86** may have any suitable cross-sectional area, and in some embodiments, the cross-sectional area of an outer crown strut **86** may be equal to or greater than the cross-sectional area of an inner crown strut **66**. In some embodiments, an outer crown **46** may have the same number of inner turns **88** and outer turns **90** as the inner crown **42**.

The outer crown inner turns **88** are located closer to the side branch center point **64** than the outer crown outer turns **90**. Each outer crown inner turn **88** may be aligned about a reference circle centered upon the side branch center point **64**, and each outer crown outer turn **90** may be aligned upon another reference circle centered upon the side branch center point **64**. Thus, each outer crown inner turn **88** may be located the same distance from the side branch center point **64** as all other outer crown inner turns **88**, and each outer crown outer turn **90** may be located the same distance from the side branch center point **64** as all other outer crown outer turns **90**. In some embodiments, a peak of an outer crown inner turn **88** may point radially inwardly toward the side branch center point **64**. A peak of an outer crown outer turn **90** may point radially outwardly away from the side branch center point **64**.

In some embodiments, inner crown turns **68**, **70** may be aligned with outer crown turns **88**, **90** in a side branch radial direction. For example, as shown in FIG. **1**, inner crown outer turns **70** may be aligned with outer crown inner turns **88**, and inner crown inner turns **68** may be aligned with outer crown outer turns **90** in a side branch radial direction. In other embodiments, inner crown outer turns **70** may be aligned with outer crown outer turns **90**, and inner crown inner turns **68** may be aligned with outer crown inner turns **88** in a side branch radial direction. It should be noted that such alignment may change during side branch expansion, as the inner crown **42** may rotate with respect to the outer crown **46** during side branch expansion as described herein below.

In some embodiments, the length of inner crown struts **66** may be greater than the length of outer crown struts **86**. In some embodiments, the length of a perimeter of the inner crown **42** may be equal to or greater than the length of a perimeter of the outer crown **46**. Desirably, when comparing perimeter lengths, the inner crown **42** and the outer crown **46** are measured at corresponding and/or similar locations. For example, inner perimeter measurements or outer perimeter measurements may be taken for both the inner crown **42** and the outer crown **46**.

The side branch structure **40** further comprises a plurality of side branch connectors **60**. Each side branch connector **60** connects to the outer crown **46** at one end and to the inner crown **42** at the other end. A side branch connector **60** may have any suitable size, shape and cross-sectional area. In some embodiments, the cross-sectional area of a side branch connector **60** is less than the cross-sectional area of an inner crown strut **66**.

In some embodiments, each side branch connector **60** may have a similar shape, and in some other embodiments, various side branch connectors **60** may have different shapes. A side branch connector **60** may have curvature along its length, and thus may include at least one peak **63**. In some embodiments, a side branch connector **60** may include multiple peaks **63** along its length, which may have different orientations and may be located on opposite sides of an inflection point **65**. In some embodiments, a side branch connector **60** may have at least a portion of its length, or all of its length, oriented in a side branch non-radial direction when the side branch structure **40** is unexpanded. The side branch connectors **60** may reorient upon expansion of the side branch structure **40**.

Each side branch connector **60** may connect to any portion of the outer crown **46** and to any portion of the inner crown **42**. In some embodiments, side branch connectors **60** connect to turns **68**, **70**, **88**, **90** of the inner crown **42** and the outer crown **46**. In some embodiments, a side branch connector **60** connects between an outer crown outer turn **90** and an inner crown outer turn **70**. In some embodiments, each side branch connector **60** is oriented such that a first end and a second end of a given connector **60** are not aligned in a side branch radial direction.

The side branch structure **40** further defines a plurality of side branch cells **56**. In some embodiments, a side branch cell **56** may be bounded by a portion of the inner crown **42**, a side branch connector **60**, a portion of the outer crown **46** and another side branch connector **60**.

In some embodiments, each side branch cell **56** may have a similar shape. In some embodiments, the shape of one side branch cell **56** may comprise the shape of another side branch cell **56** rotated about the side branch center point **64**, for example being rotated by 90°, 180° and/or 270°.

Expansion characteristics of the side branch structure **40** are discussed below with respect to FIGS. **4-6**.

FIG. **2** shows another embodiment of a flat pattern for a stent **10** having a side branch structure **40**. The side branch structure **40** may comprise an inner crown **42**, an intermediate crown **44**, a plurality of inner side branch connectors **61**, an outer crown **46** and a plurality of outer side branch connectors **62**. The side branch structure **40** may be generally centered about a side branch center point **64**.

The inner crown **42** may be similar to the inner crown **42** as described with respect to FIG. **1**, and thus may comprise inner crown struts **66**, inner crown turns **68**, **70** and petals **48**.

The intermediate crown **44** may have any suitable shape and may form a closed loop that extends around the inner crown **42**. The intermediate crown **44** may be centered about the side branch center point **64**.

In some embodiments, the intermediate crown **44** may comprise a plurality of intermediate crown struts **76** connected between alternating intermediate crown inner turns **78** and intermediate crown outer turns **80**. Each intermediate crown strut **76** is connected at one end to an intermediate crown inner turn **78** and at another end to an intermediate crown outer turn **80**. Each intermediate crown strut **76** may be straight along its length. Each intermediate crown strut **76** may have any suitable cross-sectional area, and in some embodiments, the cross-sectional area of an intermediate crown strut **76** may be equal to or greater than the cross-sectional area of an inner crown strut **66**. In some embodiments, an intermediate crown **44** may have the same number of inner turns **88** and outer turns **80** as the inner crown **42**.

The intermediate crown inner turns **78** are located closer to the side branch center point **64** than the intermediate crown outer turns **80**. Each intermediate crown inner turn **78** may be aligned about a reference circle centered upon the side branch center point **64**, and each intermediate crown outer turn **80** may be aligned upon another reference circle centered upon the side branch center point **64**. Thus, each intermediate crown inner turn **78** may be located the same distance from the side branch center point **64** as all other intermediate crown inner turn **78**, and each intermediate crown outer turn **80** may be located the same distance from the side branch center point **64** as all other intermediate crown outer turns **80**. In some embodiments, a peak of an intermediate crown inner turn **78** may point radially inwardly toward the side branch center point **64**. A peak of an intermediate crown outer turn **80** may point radially outwardly away from the side branch center point **64**.

In some embodiments, inner crown turns **68**, **70** may be aligned with intermediate crown turns **78**, **80** in a side branch radial direction. For example, as shown in FIG. **2**, inner crown outer turns **70** may be aligned with intermediate crown inner turns **78**, and inner crown inner turns **68** may be aligned with intermediate crown outer turns **80** in a side branch radial direction. In other embodiments, inner crown outer turns **70** may be aligned with intermediate crown outer turns **80**, and inner crown inner turns **68** may be aligned with intermediate crown inner turns **78** in a side branch radial direction. It should be noted that such alignment may change during side branch expansion, as the inner crown **42** may rotate with respect to the intermediate crown **44** during side branch expansion as described herein below.

In some embodiments, the length of inner crown struts **66** may be greater than the length of intermediate crown struts **76**. In some embodiments, the length of a perimeter of the inner crown **42** may be equal to or greater than the length of a perimeter of the intermediate crown **44**. Desirably, when comparing perimeter lengths, the inner crown **42** and the intermediate crown **44** are measured at corresponding and/or similar locations. For example, inner perimeter measurements or outer perimeter measurements may be taken for both the inner crown **42** and the intermediate crown **44**.

The outer crown **46** may have any suitable shape and may form a closed loop that extends around the intermediate crown **44**. The outer crown **46** may be centered about the side branch center point **64**. The outer crown **46** may be similar to the outer crown **46** as described with respect to FIG. **1**, and thus may comprise outer crown struts **86**, outer crown inner turns **88** and outer crown outer turns **90**. In some embodiments, an outer crown **46** may have the same number of inner turns **88** and outer turns **90** as the intermediate crown **44**.

In some embodiments, outer crown turns **88**, **90** may be aligned with intermediate crown turns **78**, **80** in a side branch radial direction. For example, as shown in FIG. **2**, outer crown outer turns **90** may be aligned with intermediate crown inner turns **78**, and outer crown inner turns **88** may be aligned with intermediate crown outer turns **80** in a side branch radial direction. In other embodiments, outer crown outer turns **90** may be aligned with intermediate crown outer turns **80**, and outer crown inner turns **88** may be aligned with intermediate crown inner turns **78** in a side branch radial direction. It should be noted that such alignment may change during side branch expansion, as the intermediate crown **44** may rotate with respect to the outer crown **46** during side branch expansion as described herein below.

In some embodiments, the shape and orientation of the intermediate crown **44** may be chosen to maximize the size (i.e. distance across or diameter) of the intermediate crown **44** within the outer crown **46**. In some embodiments, the shape and orientation of the intermediate crown **44** may further be chosen to allow a maximum amount of area within the intermediate crown **44**, and thus may allow room to maximize the perimeter of the inner crown **42**.

The side branch structure **40** comprises a plurality of inner side branch connectors **61**. Each inner side branch connector **61** connects to the intermediate crown **44** at one end and to the inner crown **42** at the other end. An inner side branch connector **61** may have any suitable size, shape and cross-sectional area. In some embodiments, the cross-sectional area of an inner side branch connector **61** is less than the cross-sectional area of an inner crown strut **66**. The cross-sectional area of an inner side branch connector **61** may also be less than the cross-sectional area of an intermediate crown strut **76**.

In some embodiments, each inner side branch connector **61** may have a similar shape, and in some other embodiments, various inner side branch connectors **61** may have different shapes. As shown in FIG. **2**, an inner side branch connector **61** may be straight along its length.

An inner side branch connector **61** may have at least a portion of its length, or all of its length, oriented in a side branch non-radial direction when the side branch structure **40** is unexpanded. The inner side branch connectors **61** may reorient upon expansion of the side branch structure **40**.

Each inner side branch connector **61** may connect to any portion of the intermediate crown **44** and to any portion of the inner crown **42**. In some embodiments, inner side branch connectors **61** connect to turns **68**, **70**, **78**, **80** of the inner crown **42** and the intermediate crown **44**. In some embodiments, an inner side branch connector **61** connects between an intermediate crown outer turn **80** and an inner crown outer turn **70**. In some embodiments, an inner side branch connector **61** connects between an intermediate crown inner turn **78** and an inner crown outer turn **70**.

The side branch structure **40** further defines a plurality of inner side branch cells **52**. In some embodiments, an inner

side branch cell **52** may be bounded by a portion of the inner crown **42**, an inner side branch connector **61**, a portion of the intermediate crown **44** and another inner side branch connector **61**.

In some embodiments, each inner side branch cell **52** may have a similar shape. In some embodiments, the shape of one inner side branch cell **52** may comprise the shape of another inner side branch cell **52** rotated about the side branch center point **64**, for example being rotated by 90°, 180° and/or 270°.

The side branch structure **40** comprises a plurality of outer side branch connectors **62**. Each outer side branch connector **62** connects to the intermediate crown **44** at one end and to the outer crown **46** at the other end. An outer side branch connector **62** may have any suitable size, shape and cross-sectional area. In some embodiments, the cross-sectional area of an outer side branch connector **62** is less than the cross-sectional area of an intermediate crown strut **76**.

In some embodiments, each outer side branch connector **62** may have a similar shape, and in some other embodiments, various outer side branch connectors **62** may have different shapes. As shown in FIG. **2**, an outer side branch connector **62** may be straight along its length.

An outer side branch connector **62** may have at least a portion of its length, or all of its length, oriented in a side branch non-radial direction when the side branch structure **40** is unexpanded. The outer side branch connectors **62** may reorient upon expansion of the side branch structure **40**.

Each outer side branch connector **62** may connect to any portion of the intermediate crown **44** and to any portion of the outer crown **46**. In some embodiments, outer side branch connectors **62** connect to turns **78**, **80**, **88**, **90** of the intermediate crown **44** and the outer crown **45**. In some embodiments, an outer side branch connector **62** connects between an intermediate crown outer turn **80** and an outer crown outer turn **90**.

In some embodiments, inner side branch connectors **61** and outer side branch connectors **62** may connect to intermediate crown outer turns **80**. In some embodiments, an inner side branch connector **61** and an outer side branch connector **62** may connect to a common intermediate crown outer turn **80**.

The side branch structure **40** further defines a plurality of outer side branch cells **54**. In some embodiments, an outer side branch cell **54** may be bounded by a portion of the intermediate crown **44**, an outer side branch connector **62**, a portion of the outer crown **46** and another outer side branch connector **62**.

In some embodiments, each outer side branch cell **54** may have a similar shape. In some embodiments, the shape of one outer side branch cell **54** may comprise the shape of another outer side branch cell **54** rotated about the side branch center point **64**, for example being rotated by 90°, 180° and/or 270°.

FIG. **3** shows another embodiment of a flat pattern for a stent **10**. The serpentine bands **20**, connector struts **16**, inner crown **42**, intermediate crown **44** and outer crown **46** may be similar to the structure illustrated and described with respect to FIG. **2**.

In some embodiments, the inner side branch connectors **61** and/or the outer side branch connectors **62** may include curvature and thus may include at least one peak **63**. In some embodiments, a side branch connector **61**, **62** may include multiple peaks **63** along its length, which may have different orientations and may be located on opposite sides of an inflection point **65**.

Including curvature in the side branch connectors may allow for longer side branch connectors, and may allow for a longer side branch connector to be oriented within the area available between the various crowns **42**, **44**, **46**.

Referring to FIGS. **4-6**, the stent **10** of FIG. **1** is shown at various stages of side branch expansion.

FIG. **4** shows the side branch structure **40** in a first or unexpanded state, wherein all of the side branch structure **40** is oriented within the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. The area of the inner side branch cell **50** defined within the inner crown **42** overlaps the area defined within the outer crown **46**. At least a substantial portion of the length of the side branch connectors **60** may be oriented in a side branch non-radial direction.

FIG. **5** shows the side branch structure **40** in a second or expanded state. The side branch structure **40** may be expanded, for example, by a catheter balloon or any other suitable side branch expansion device. In some embodiments, an expansion device may comprise a catheter balloon having an auxiliary inflatable portion, for example as disclosed in US Published Patent Application No. 2005/0060027 to Khenansho et al., the entire disclosure of which is hereby incorporated herein by reference in its entirety. The expansion device may place forces that are directed in a stent radial outward direction upon any portion of the side branch structure **40**, and desirably upon the inner crown **42**, and more desirably upon the inner crown struts **66** and inner crown inner turns **68**.

During side branch expansion, the inner crown **42** displaces outwardly in a stent radial direction **82** and moves out of the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. The stent radial direction **82** being referred to may pass through the side branch center point **64** (see FIG. **1**). After the outward displacement, the area defined within the inner crown **42** does not overlap the area defined within the outer crown **46**.

The inner crown **42** may further rotate with respect to the outer crown **46** and with respect to the rest of the stent **10** during side branch expansion. In some embodiments, an inner crown outer turn **70** that was not aligned with an outer crown outer turn **90** in a side branch radial direction prior to side branch expansion may become aligned with an outer crown outer turn **90** in a side branch radial direction as the inner crown **42** rotates.

The side branch connectors **60** reorient during side branch expansion and allow the inner crown **42** to displace outwardly. After side branch expansion, the side branch connectors **60** may extend out of the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. The side branch connectors **60** may further be oriented, or may have a length component oriented, in a side branch radial direction. When three dimensions are taken into consideration, a line having a length component in the plane of the side branch structure oriented in a side branch radial direction may be described as being oriented in a side branch radial direction. Due to the three-dimensional nature of the stent **10**, after side branch expansion a side branch connector **60** may have a first length component **96** that is oriented in a stent radial direction and a second length component **98** that is oriented in a side branch radial direction. In embodiments where the side branch connectors **60** include curvature, they may straighten upon side branch expansion.

FIG. **6** shows the side branch structure **40** in a third or deployed state, wherein each petal **48** defined by the inner crown **42** has unfolded outwardly. When the inner crown **42** has displaced outwardly in a stent radial direction the maximum amount allowed by the side branch connectors **60**, continued outward force applied by the expansion device desirably causes the petals **48** to unfold. Each inner crown inner turn **68** may displace outward in both stent radial and side branch radial directions upon petal **48** deployment.

As shown in FIGS. **5** and **6**, the outer crown **46** remains within the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10** throughout side branch expansion and petal **48** deployment.

In some embodiments, a side branch expansion device that applies outward forces to the inner crown **42** does not distinguish between the stages of expansion illustrated in FIGS. **4-6**. Therefore, it is likely that similar forces applied by a similar portion of an expansion device will work to both displace the inner crown **42** outwardly and to unfold the petals **48**.

The inner crown **42** and the side branch connectors **60** are desirably designed such that side branch expansion forces applied to the inner crown **42** will first work to displace the inner crown **42** outwardly. After the side branch connectors **60** have reoriented and the inner crown **42** is located at an outward displacement limit, the expansion forces then cause the petals **48** to unfold. Thus, the force required to unfold the petals **48** is desirably greater than the force required to displace the inner crown **42** and reorient the side branch connectors **60**. The various members of the side branch structure **40** may be sized and shaped to create the strength gradient necessary for such side branch expansion/deployment, for example using finite element analysis.

Stents **10** as described herein may be used to support vessel walls. The main cylindrical framework may be used to support a main branch vessel wall. The expanded and deployed side branch structure may be used to support a branch vessel. In some embodiments, side branch connectors **60** may provide scaffolding support to portions of a branch vessel or area of bifurcation, such as the carina or contralateral ostial wall. The inner crown **42** and more specifically the outwardly deployed petals **48** may further provide scaffolding support for a branch vessel.

FIG. **6** shows a slight taper in the deployed side branch structure **40**. The amount of taper may be adjusted in various embodiments to provide appropriate support for a side branch vessel. In various embodiments, the side branch structure **40** may be designed with a high amount of taper (i.e. the deployed diameter of the inner crown **42** is substantially smaller than that of the outer crown **46**), no taper (i.e. the deployed diameter of the inner crown **42** is substantially equal to that of the outer crown **46**), or even an outward taper (i.e. the deployed diameter of the inner crown **42** is larger than that of the outer crown **46**). In some embodiments, the deployed inner crown **42** may further be stretched by an appropriate deployment device to increase its deployed diameter.

FIG. **6** further shows the expanded side branch structure **40** extending from the main cylindrical framework in a direction that is generally orthogonal to the central longitudinal axis **11** of the stent **10**. In some embodiments, the expanded side branch structure may extend at a different angle to the stent **10** longitudinal axis in order to match the orientation of a branch vessel. In some embodiments, the collective general direction of extension of the side branch structure **40** may be adjusted by varying the length of individual side branch connectors **60**. For example, if the side branch connectors **60** that connect to a proximal side of the outer crown **46** are longer than the side branch connectors **60** that connect to a distal side of the outer crown **46**, the expanded side branch structure **40** may be angled in the distal direction.

Referring to FIGS. **7-10**, the stent **10** of FIG. **3** is shown at various stages of side branch expansion.

FIG. **7** shows the side branch structure **40** in a first or unexpanded state, wherein all of the side branch structure **40** is oriented within the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. The area of the inner side branch cell **50** defined within the inner crown **42** overlaps the area defined within the intermediate crown **44**. The area defined within the intermediate crown **44** overlaps the area defined within the outer crown **46**. At least a substantial portion of the length of the inner side branch connectors **61** and the outer side branch connectors **62** may be oriented in a side branch non-radial direction.

FIG. **8** shows the side branch structure **40** in a second or intermediate state following a first expansion step. An expansion device may place forces that are directed in a stent radial outward direction **82** upon any portion of the side branch structure **40**, desirably upon the intermediate crown **44** and the inner crown **42**, and more desirably upon the inner crown struts **66** and inner crown inner turns **68**. The stent radial direction **82** being referred to may pass through the side branch center point **64** (see FIG. **3**).

During side branch expansion, the intermediate crown **44**, inner crown connectors **61** and the inner crown **42** displace outwardly in a stent radial direction, and move out of the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. After the outward displacement, the area defined within the intermediate crown **44** and the area defined within the inner crown **42** do not overlap the area defined within the outer crown **46**. The intermediate crown **44**, inner crown connectors **61** and the inner crown **42** may further rotate with respect to the outer crown **46** and with respect to the rest of the stent **10** during side branch expansion. In some embodiments, an intermediate crown outer turn **80** that was not aligned with an outer crown outer turn **90** in a side branch radial direction prior to side branch expansion may become aligned with an outer crown outer turn **90** in a side branch radial direction as the intermediate crown **44** rotates.

The outer side branch connectors **62** reorient during side branch expansion and allow the intermediate crown **44** to displace outwardly. After the displacement, the outer side branch connectors **62** may extend out of the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10**. The outer side branch connectors **62** may further have a length component oriented in a side branch radial direction and another length component oriented in a stent radial direction.

In embodiments where the outer side branch connectors **62** include curvature, they may straighten upon intermediate crown **44** outward displacement.

FIG. **9** shows the side branch structure **40** in a third or expanded state following a second expansion step. The inner crown **42** is displaced outwardly in a stent radial direction and has moved out of the area defined within the intermediate crown **44**.

The inner side branch connectors **61** have reoriented and now extend out of the area defined within the intermediate crown **44**. The inner side branch connectors **61** may further have a length component oriented in a side branch radial direction and another length component oriented in a stent radial direction. In embodiments where the inner side branch connectors **61** include curvature, they may straighten as the inner crown **42** is displaced away from the intermediate crown **44**.

The inner crown **42** may further rotate with respect to the intermediate crown **44** and with respect to the rest of the stent **10**, and thus alignment between the inner crown turns **68**, **70** and the intermediate crown turns **78**, **80** may change during displacement of the inner crown **42**. The inner crown **42** may further be arranged to rotate with respect to the intermediate crown **44** in the same direction that the intermediate crown **44** rotates with respect to the outer crown **46**, or in a different

direction. Having opposite rotational orientations may be desirable, for example in order to minimize cumulative rotational stresses experienced by an expansion device. The direction of rotation of either crown **42**, **44** may be selected by varying the orientation and connection locations of the side branch connectors **61**, **62**.

In some embodiments, the structural changes described with respect to the above first and second expansion steps may occur in a different order. For example, in some embodiments, the inner crown **42** may first displace outward in a stent radial direction while the intermediate crown **44** remains within the area defined within the outer crown **46**, and then the intermediate crown **44** may displace outwardly while the inner crown **42** continues to displace outwardly. In some embodiments, the intermediate crown **44** may displace outwardly from the outer crown **46** and the inner crown **42** may displace outwardly from the intermediate crown **44** simultaneously.

FIG. **10** shows the side branch structure **40** in a fourth or deployed state, wherein each petal **48** defined by the inner crown **42** has unfolded outwardly. When the inner crown **42** has displaced outwardly in a stent radial direction the maximum amount allowed by the inner side branch connectors **61** and the outer side branch connectors **62**, continued outward force applied by the expansion device desirably causes the petals **48** to unfold. Each inner crown inner turn **68** may displace outward in both stent radial and side branch radial directions upon petal **48** deployment.

As shown in FIGS. **8-10**, the outer crown **46** remains within the area of the cylindrical plane defined by the substantially cylindrical framework of the stent **10** throughout side branch expansion and petal **48** deployment.

The various inner crown **42**, the inner side branch connectors **61** and the outer side branch connectors **62** are desirably designed such that side branch expansion forces applied to the inner crown **42** will first work to displace the inner crown **42** outwardly. After the side branch connectors **61**, **62** have reoriented and the inner crown **42** is located at an outward displacement limit, the expansion forces then cause the petals **48** to unfold. Thus, the force required to unfold the petals **48** is desirably greater than the force required to displace the inner crown **42** and reorient the side branch connectors **61**, **62**. The various members of the side branch structure **40** may be sized to create the strength gradient necessary for proper side branch expansion/deployment, for example using finite element analysis. The strength of the inner side branch connectors **61** and the outer side branch connectors **62** may further be adjusted with respect to one another to influence the timing of displacement of the intermediate crown **44** with respect to the outer crown **46** and displacement of the inner crown **42** with respect to the intermediate crown **44**.

Stents **10** as described herein may be used to support vessel walls. The main cylindrical framework may be used to support a main branch vessel wall. The expanded and deployed side branch structure may be used to support a branch vessel. In some embodiments, outer side branch connectors **62** may provide scaffolding support to portions of a branch vessel or area of bifurcation, such as the carina or contralateral ostial wall. The intermediate crown **44**, the inner side branch connectors **61**, the inner crown **42** and more specifically the outwardly deployed petals **48** may further provide scaffolding support for a branch vessel.

FIG. **10** shows a slight taper in the deployed side branch structure **40**. The amount of taper may be adjusted in various embodiments to provide appropriate support for a side branch vessel. In various embodiments, the side branch structure **40** may be designed with a high amount of taper, no taper or even a reverse taper. The amount of taper may be adjusted by adjusting the size (i.e. diameter) of the outer crown **46**, the intermediate crown **44** and the inner crown **42** with respect to one another. In some embodiments, the deployed inner crown **42** may further be stretched by an appropriate deployment device to increase its deployed diameter.

FIG. **10** further shows the expanded side branch structure **40** extending from the main cylindrical framework in a direction that is generally orthogonal to the central longitudinal axis **11** of the stent **10**. In some embodiments, the expanded side branch structure **40** may extend at a different angle to the stent **10** longitudinal axis in order to match the orientation of a side branch vessel. In some embodiments, the collective general direction of extension of the side branch structure **40** may be adjusted by varying the length of individual inner side branch connectors **61** and outer side branch connectors **62**. For example, if the outer side branch connectors **62** that connect to a proximal side of the outer crown **46** are longer than the inner side branch connectors **62** that connect to a distal side of the outer crown **46**, the expanded side branch structure **40** may be angled in the distal direction. The inner side branch connectors **61** and the outer side branch connectors **62** may further be adjusted independently from one another. For example, using outer side branch connectors **62** of the same length and inner side branch connectors **61** of different lengths may provide the expanded side branch structure **40** with a curve.

In some embodiments, the side branch connectors **61**, **62** may all connect between outer turns **70**, **80**, **90** of the various crown structures **42**, **44**, **46** in order to maximize the expanded diameter of the side branch structure **40**.

The invention is further directed to methods of making stents **10** as described herein. The invention is further directed to methods of delivering and expanding/deploying stents **10** as described herein.

A stent **10** may be delivered to a deployment location, for example using a delivery catheter. In some embodiments, the stent **10** may be delivered to a vessel bifurcation and oriented such that the side branch structure **40** will extend into a branch vessel during side branch expansion. The substantially cylindrical framework of the stent **10** may be expanded in diameter, for example by inflating a catheter balloon. The side branch structure **40** may further be expanded and deployed as described herein using any suitable method, such as an auxiliary inflatable side branch portion of a balloon catheter.

In some embodiments, a stent **10** may be self-expanding, for example being made from a shape memory material. A self-expanding stent **10** may normally assume an expanded configuration wherein the side branch structure is expanded and deployed. A self-expanding stent **10** may be delivered to a deployment location in an unexpanded configuration, for example being constrained by a sheath. Upon removal of the constrainment device, the stent **10** may assume its expanded configuration.

In some embodiments the stent, the delivery system or other portion of the assembly may include one or more areas, bands, coatings, members, etc. that is (are) detectable by imaging modalities such as X-Ray, MRI, ultrasound, etc. In some embodiments at least a portion of the stent and/or adjacent assembly is at least partially radiopaque.

In some embodiments the at least a portion of the stent is configured to include one or more mechanisms for the delivery of a therapeutic agent. Often the agent will be in the form of a coating or other layer (or layers) of material placed on a surface region of the stent, which is adapted to be released at the site of the stent's implantation or areas adjacent thereto.

A therapeutic agent may be a drug or other pharmaceutical product such as non-genetic agents, genetic agents, cellular material, etc. Some examples of suitable non-genetic therapeutic agents include but are not limited to: anti-thrombogenic agents such as heparin, heparin derivatives, vascular cell growth promoters, growth factor inhibitors, Paclitaxel, etc. Where an agent includes a genetic therapeutic agent, such a genetic agent may include but is not limited to: DNA, RNA and their respective derivatives and/or components; hedgehog proteins, etc. Where a therapeutic agent includes cellular material, the cellular material may include but is not limited to: cells of human origin and/or non-human origin as well as their respective components and/or derivatives thereof. Where the therapeutic agent includes a polymer agent, the polymer agent may be a polystyrene-polyisobutylene-polystyrene triblock copolymer (SIBS), polyethylene oxide, silicone rubber and/or any other suitable substrate.

The invention further comprises various embodiments of stents **10** as described in the following numbered paragraphs:

1. A stent comprising:
   - a plurality of struts arranged to form a substantially cylindrical expandable framework, the struts defining a plurality of cells; and
   - a side branch structure comprising:
     - an outer crown comprising a plurality of outer crown struts arranged to form a closed loop, the outer crown defining a side branch area;
     - an intermediate crown comprising a plurality of intermediate crown struts arranged to form a closed loop, the intermediate crown oriented within the outer crown;
     - a plurality of outer side branch connectors, each outer side branch connector having a first end connected to the intermediate crown and a second end connected to the outer crown;
     - an inner crown comprising a plurality of inner crown struts arranged to form a closed loop, the inner crown defining an inner side branch cell having a shape different from the shape of any other cell, the inner crown oriented within the intermediate crown; and
     - a plurality of inner side branch connectors, each inner side branch connector having a first end connected to the inner crown and a second end connected to the intermediate crown;
   - wherein upon a first expansion step of said side branch structure, the entire inner crown displaces outwardly from said cylindrical expandable framework in a stent radial direction.
2. The stent of paragraph 1, wherein the entire intermediate crown displaces outwardly from said cylindrical expandable framework in a stent radial direction upon said first expansion step.
3. The stent of paragraph 2, wherein upon a second expansion step, the entire inner crown displaces outwardly from said intermediate crown in a stent radial direction.
4. The stent of paragraph 3, wherein a first inner side branch connector is oriented in a side branch non-radial direction when said side branch structure is unexpanded.
5. The stent of paragraph 4, wherein said first inner side branch connector includes curvature along its length.
6. The stent of paragraph 4, wherein said first inner side branch connector reorients in a side branch radial direction upon said second expansion step of said side branch structure.
7. The stent of paragraph 3, wherein the inner crown further comprises a plurality of petals, each petal rotating to unfold outwardly in a stent radial direction upon petal deployment.
8. The stent of paragraph 7, wherein each petal unfolds outwardly in a side branch radial direction upon petal deployment.
9. The stent of paragraph 7, wherein a force applied to the stent by a catheter balloon required to displace the intermediate crown outwardly during the first expansion step is less than the force required to displace the inner crown outwardly with respect to the intermediate crown during the second expansion step.
10. The stent of paragraph 9, wherein the force required to displace the inner crown outwardly with respect to the intermediate crown during the second expansion step is less than the force required to unfold the petals outwardly during petal deployment.
11. The stent of paragraph 3, wherein the inner crown rotates with respect to the outer crown during said first expansion step.
12. The stent of paragraph 2, wherein the intermediate crown rotates with respect to the outer crown during said first expansion step.
13. The stent of paragraph 12, wherein the inner crown rotates with the intermediate crown during said first expansion step.
14. The stent of paragraph 3, wherein the inner crown rotates with respect to the intermediate crown during said second expansion step.
15. The stent of paragraph 1, wherein the inner crown rotates with respect to the outer crown during said first expansion step
16. The stent of paragraph 1, the side branch structure in an unexpanded state defining a plurality of outer side branch cells, each outer side branch cell being partially bounded by at least one outer crown strut, at least one intermediate crown strut, a first outer side branch connector and a second outer side branch connector.
17. The stent of paragraph 16, wherein the shape of an outer side branch cell comprises the shape of another outer side branch cell rotated about a side branch center point.
18. The stent of paragraph 16, the side branch structure further defining a plurality of intermediate side branch cells, each intermediate side branch cell being partially bounded by at least one intermediate crown strut, at least one inner crown strut, a first inner side branch connector and a second inner side branch connector.
19. The stent of paragraph 18, wherein the shape of an intermediate side branch cell comprises the shape of another intermediate side branch cell rotated about the side branch center point.
20. The stent of paragraph 1, wherein a perimeter of the inner crown is equal to or greater than a perimeter of the intermediate crown.
21. The stent of paragraph 1, wherein a perimeter of the inner crown is equal to or greater than a perimeter of the outer crown.
22. The stent of paragraph 1, wherein the outer crown remains in said cylindrical expandable framework after said first expansion step.
23. The stent of paragraph 3, wherein the outer crown remains in said cylindrical expandable framework after said second expansion step.
24. The stent of paragraph 1, wherein a first outer side branch connector is oriented in a side branch non-radial direction when said side branch structure is unexpanded.

25. The stent of paragraph 24, wherein said first outer side branch connector includes curvature along its length.
26. The stent of paragraph 24, wherein said first outer side branch connector reorients in a side branch radial direction upon said first expansion step.
27. The stent of paragraph 1, wherein a cross-sectional area of an inner crown strut is greater than a cross-sectional area of an inner side branch connector.
28. The stent of paragraph 1, wherein a cross-sectional area of an inner side branch connector is greater than a cross-sectional area of an outer side branch connector.
29. The stent of paragraph 1, the inner crown further comprising a plurality of inner crown inner turns and a plurality of inner crown outer turns, each inner crown strut connected at one end to an inner crown inner turn and at another end to an inner crown outer turn, the inner turns located closer to a side branch center point than the outer turns.
30. The stent of paragraph 29, wherein each inner crown outer turn is located an equal distance from the side branch center point.
31. The stent of paragraph 29, wherein each inner crown strut is straight along its length and substantially oriented in a side branch radial direction.
32. The stent of paragraph 29, the intermediate crown further comprising a plurality of intermediate crown inner turns and a plurality of intermediate crown outer turns, each intermediate crown strut connected at one end to an intermediate crown inner turn and at another end to an intermediate crown outer turn, the intermediate crown inner turns located closer to a side branch center point than the intermediate crown outer turns.
33. The stent of paragraph 32, wherein a first inner side branch connector is connected at one end to an inner crown outer turn and connected at the other end to an intermediate crown inner turn.
34. The stent of paragraph 32, wherein a first outer side branch connector is connected at one end to an outer crown outer turn and connected at the other end to an intermediate crown outer turn.

The above disclosure is intended to be illustrative and not exhaustive. This description will suggest many variations and alternatives to one of ordinary skill in this art. The various elements shown in the individual figures and described above may be combined or modified for combination as desired. All these alternatives and variations are intended to be included within the scope of the claims where the term "comprising" means "including, but not limited to".

Further, the particular features presented in the dependent claims can be combined with each other in other manners within the scope of the invention such that the invention should be recognized as also specifically directed to other embodiments having any other possible combination of the features of the dependent claims. For instance, for purposes of claim publication, any dependent claim which follows should be taken as alternatively written in a multiple dependent form from all prior claims which possess all antecedents referenced in such dependent claim if such multiple dependent format is an accepted format within the jurisdiction (e.g. each claim depending directly from claim **1** should be alternatively taken as depending from all previous claims). In jurisdictions where multiple dependent claim formats are restricted, the following dependent claims should each be also taken as alternatively written in each singly dependent claim format which creates a dependency from a prior antecedent-possessing claim other than the specific claim listed in such dependent claim below.

This completes the description of the preferred and alternate embodiments of the invention. Those skilled in the art may recognize other equivalents to the specific embodiment described herein which equivalents are intended to be encompassed by the claims attached hereto.

The invention claimed is:

1. A balloon expandable stent in an unexpanded configuration comprising:

a plurality of struts arranged to form a substantially cylindrical expandable framework, the struts defining a plurality of cells; and

a side branch structure comprising:

an outer crown comprising a plurality of outer crown struts arranged to form a closed loop, the outer crown defining a side branch area;

an inner crown comprising a plurality of inner crown struts and inner crown turns arranged to form a closed loop, the inner crown turns comprising inner turns and outer turns, the struts and inner turns defining petals, the inner crown defining an inner side branch cell having a shape different from the shape of any other cell, the inner turns located closer to a centerpoint of the inner side branch cell than the outer turns; and

a plurality of side branch connectors made from the same material as the inner crown, each side branch connector having a first end connected to an outer turn of the inner crown and a second end connected to the outer crown, each side branch connector comprising an inflection point, each side branch connector oriented such that said first end and said second end are not aligned in a side branch radial direction.

2. The stent of claim **1**, wherein upon expansion of said side branch structure, the inner crown rotates about a center point of the side branch structure.

3. The stent of claim **1**, the side branch structure in an unexpanded state defining a plurality of outer side branch cells, each outer side branch cell being partially bounded by at least one outer crown strut, at least one inner crown strut, a first side branch connector and a second side branch connector, wherein the shape of an outer side branch cell comprises the shape of another outer side branch cell rotated about a center point of the side branch structure.

4. The stent of claim **1**, wherein a perimeter of the inner crown is equal to or longer than a perimeter of the outer crown.

5. The stent of claim **1**, wherein the outer crown remains in said cylindrical expandable framework after expansion of said side branch structure.

6. The stent of claim **1**, wherein at least a portion of a first side branch connector is oriented in a side branch non-radial direction when said side branch structure is unexpanded.

7. The stent of claim **6**, wherein said first side branch connector reorients upon expansion of said side branch structure to have a length component oriented in a side branch radial direction.

8. The stent of claim **1**, wherein a cross-sectional area of an inner crown strut is greater than a cross-sectional area of a side branch connector.

9. The stent of claim **1**, wherein each petal rotates to unfold outwardly in a stent radial direction upon petal deployment.

10. The stent of claim **1**, wherein each side branch connector comprises a first curved portion and a second curved portion located on opposite sides of said inflection point.

11. The stent of claim **1**, wherein upon expansion of said side branch structure, the entire inner crown displaces outwardly from said cylindrical expandable framework in a stent radial direction.

12. A balloon expandable stent in an unexpanded configuration comprising:

a plurality of struts arranged to form a substantially cylindrical expandable framework, the struts defining a plurality of cells; and

a side branch structure comprising:

an outer crown comprising a plurality of outer crown struts arranged to form a closed loop, the outer crown defining a side branch area;

an inner crown comprising a plurality of inner crown struts and inner crown turns arranged to form a closed loop, the inner crown turns comprising inner turns and outer turns, the struts and inner turns defining petals, the inner crown defining an inner side branch cell having a shape different from the shape of any other cell, the inner turns located closer to a centerpoint of the inner side branch cell than the outer turns; and

a plurality of side branch connectors made from the same material as the inner crown, each side branch connector having a first end connected to an outer turn of the inner crown and a second end connected to the outer crown, each side branch connector comprising an inflection point;

wherein said plurality of side branch connectors comprises a first side branch connector having a length that is different from the length of a second side branch connector.

13. The stent of claim 1, wherein each inner crown outer turn is located an equal distance from the side branch center point.

14. The stent of claim 1, the outer crown further comprising a plurality of outer crown inner turns and a plurality of outer crown outer turns, each outer crown strut connected at one end to an outer crown inner turn and at another end to an outer crown outer turn, the outer crown inner turns located closer to a side branch center point than the outer crown outer turns, wherein each side branch connector is connected at the second end to an outer crown outer turn.

15. The stent of claim 14, wherein each side branch connector comprises a length that is greater than two outer crown struts.

16. A method comprising:

providing the stent of claim 1;

orienting the stent within a main bodily vessel with the side branch structure adjacent to a branch vessel; and

expanding said side branch structure, wherein said inner crown displaces outwardly from said cylindrical expandable framework and into said branch vessel.

17. The method of claim 16, wherein the expanding step further comprises orienting an inflation device within an internal lumen of the stent adjacent to the side branch structure and inflating the inflation device to thereby cause the inner crown to displace outwardly.

* * * * *